

Wöhler DT 310 Diferencijalni Termometar



PRIMJENA

- Jednostavno mjerene diferencijalne temperature
- Mjerenje temperature na dolazu i odlazu vodenih i dimovodnih linija

PREDNOSTI

- Prikaz diferencijalne temperature (potrebne dvije sonde)
- Simultani prikaz mjernja oda dvije temperature
- Opcijske temperature sonde, tip K, J, T
- Run / Hold Funkcija
- Osvjetljenje zaslona
- MIN i MAX vrijednosti s datumom i vremenom

TEHNIČKI PODACI

Rezolucija

K	-200...650 °C	0.1 °C
	640...1370 °C	1 °C
J	-200...500 °C	0.1 °C
	490...760 °C	1 °C
T	cijeli opseg	0.1 °C

Točnost

K	-200...1370 °C ± 0.3 % f.m. + 0.7 °C
J	-200...760 °C ± 0.3 % f.m. + 0.7 °C
T	-200...390 °C ± 0.3 % f.m. + 0.7 °C

Napajanje.....1 x 9 V Bblok baterija

Vlaga.....0...85 % RH (bez kondenzacije)

Radnatemperatura.....0...50 °C

Dimenzije.....181 x 72 x 32 mm (LxWxT)



Wöhler DT 310 Diferencijalni Termometar

U isporuci:

Wöhler DT 310

2 kontaktne sonde (type K)

baterija

plastični kofer

Part no. 6622 I

Dodaci

Part no.



Special Wall Temperature Probe Type W-02"

za Wöhler A 400 ili Wöhler DT 310

4651 I



Surface temp. probe TF2

za Wöhler A 500 / DT 310

Termoelement tip K, do max. 500°C / 932°F

6626 I



Surface temp. probe TF3 angulate

za Wöhler A 500 / DT 310

Termoelement tip K, do max. 500°C / 932°F

6628 I



Penetration temp. probe TF4

za Wöhler A500 / DT 310

Termoelement tip K, do max. 600°C / 1112°F

6629 I



Flue gas temp. probe TF5

za Wöhler A 500 / DT 310

Termoelement tip K, do max. 900°C / 1652°F

6635 I



Surface Temperature Probe

za Wöhler DT 310 / A 400PRO / DC 410Flow

klješta, opseg do 100°C, za cijevi 6 – 35 mm Ø

6679 I