

HD 2256.2

BENCH-TOP pH AND CONDUCTIVITY METER

The HD2256.2 is a bench top instrument for electrochemical measures: **pH**, **conductivity** and **temperature**. It is fitted with a large backlit LCD display. The HD2256.2 measures **pH**, **mV**, **redox potential (ORP)** with pH, redox electrodes or electrodes with separate reference. **Conductivity and resistivity** in liquids, **total dissolved solids (TDS)** and **salinity** with combined 4-ring and 2-ring conductivity/temperature probes. The conductivity probes can have a direct input or with SICRAM module. The inputs are separate. AI models are fitted with input for the measurement of **temperature** with Pt100 or Pt1000 immersion, penetration or contact probes. The temperature probes are equipped with an automatic recognition module and factory calibration data are stored inside.

- The pH electrode calibration can be carried out on one or five points and the calibration sequence can be chosen from a list of 13 buffers. Temperature compensation can be automatic or manual.

- The conductivity probe calibration can be performed automatically with automatically detected conductivity calibration solutions: 147 μ S/cm, 1413 μ S/cm, 12880 μ S/cm or 111800 μ S/cm or manually with calibration solutions having different values.

- Conductivity, dissolved oxygen and temperature probes fitted with SICRAM module can store factory and calibration data inside.

The data can be transferred from the instrument connected to a PC via the multi-standard RS232C serial port and USB 2.0. The storing parameters can be configured using the menu. The RS232C serial port can be used to transfer the acquired measurements to a 24 column portable printer in real time (HD40.1 or HD40.2).

The instruments equipped with **HD22BT** (Bluetooth) option can transfer data without any connection to a PC or printer fitted with Bluetooth input or through Bluetooth/RS232C converter. The software DeltaLog11 allows instrument management and configuration, and data processing on PC.

The instruments have IP66 protection degree.

Technical characteristics HD2256.2

pH - mV - X - Ω - TDS - NaCl - °C - °F

Instrument

Dimensions (Length x Width x Height) 265x185x70mm

Weight 490g

Materials ABS, rubber

Display Back lighted, matrix point display.
240x64 points, visible area: 128x35mm

Operating conditions

Working temperature -5 ... 50°C

Storage temperature -25 ... 65°C

Working relative humidity 0 ... 90% R.H. without condensate

Protection degree IP66

Power

Mains adapter (cod. SWD10) 12Vdc/1A

For supplying of electrode holder with built-in stirrer HD22.2

Security of memorized data

Unlimited

Time


Date and hour

Real time schedule with backup battery 3.6V - 1/2AA
1min/month max drift

Measured values storing

Quantity 2000 screens

Storage interval 1s ... 999s





| | | | |
|--|---|--|--|
| <i>Calibration storage</i> | | <i>Measurement of resistivity by instrument</i> | <i>Resolution</i> |
| Quantity | Last 8 calibrations of each physical quantity | Measuring range (Kcell=0.01) Up to 1GΩ·cm Measuring range (Kcell=0.1) Up to 100MΩ·cm Measuring range (K cell=1) 5.0...199.9Ω·cm 200...999Ω·cm 1.00k...19.99kΩ·cm 20.0k...99.9kΩ·cm 100k...999kΩ·cm 1...10MΩ·cm 0.5...5.0Ω·cm | (*) (*) 0.1Ω·cm 1Ω·cm 0.01kΩ·cm 0.1kΩ·cm 1kΩ·cm 1MΩ·cm 0.1Ω·cm |
| <i>RS232C serial interface</i> | | Measuring range (Kcell=10) Accuracy (resistivity) | ±0.5% ±1digit |
| Type | RS232C electrically isolated | | |
| Baud rate | Can be set from 1200 to 115200 baud | | |
| Data bit | 8 | | |
| Parity | None | | |
| Stop bit | 1 | | |
| Flow Control | Xon/Xoff | | |
| Length of serial cable | Max 15m | | |
| <i>USB Interface</i> | | <i>Measurement of total dissolved solids (with coefficient χ/TDS=0.5)</i> | |
| Type | 1.1 - 2.0 electrically isolated | Measuring range (Kcell=0.01) 0.00...1.999mg/l Measuring range (Kcell=0.1) 0.00...19.99mg/l Measuring range (K cell=1) 0.0...199.9 mg/l 200...1999 mg/l 2.00...19.99 g/l 20.0...199.9 g/l | 0.005mg/l 0.05mg/l 0.5 mg/l 1 mg/l 0.01 g/l 0.1 g/l |
| <i>Bluetooth Interface</i> | optional | Measuring range (Kcell=10) Accuracy (total dissolved solids) | 1 g/l |
| <i>Connections</i> | | | |
| Input for temperature probes with SICRAM modules⑤ | 8-pole male DIN45326 connector | | |
| pH/mV input ① | BNC female | | |
| Input for SICRAM module pH/ temperature ③ | 8-pole male DIN45326 connector | | |
| 2/4 electrode direct conductivity input ⑧ | 8-pole male DIN45326 connector | | |
| Input conductivity electrodes with SICRAM module⑦ | 8-pole male DIN45326 connector | | |
| Serial interface | DB9 connector (9-pole male) | | |
| USB interface | USB connector type B | | |
| Bluetooth | Optional | | |
| Mains adapter | 2-pole connector (Ø5.5mm-2.1mm). Positive at centre | | |
| Outlet for power supply of electrode holder with built-in magnetic stirrer | 2-pole connector (Ø5.5mm-2.1mm). Positive at centre (output 12Vdc/200mA max). | | |
| <i>pH measurement by instrument</i> | | <i>Measurement of salinity by instrument</i> | |
| Measuring range | -9.999...+19.999pH | Measuring range 0.000...1.999g/l 2.00...19.99g/l 20.0...199.9 g/l | 1mg/l 10mg/l 0.1 g/l |
| Resolution | 0.01 o 0.001pH selectable from menu | | |
| Accuracy | ±0.001pH ±1digit | | |
| Input impedance | >10 ¹² Ω | | |
| Calibration error @25°C | IOffsetl > 20mV Slope > 63mV/pH o Slope < 50mV/pH Sensitivity > 106.5% or Sensitivity < 85% | | |
| Calibration points | Up to 5 points with 13 automatically detected buffer solutions | Accuracy (salinity) ±0.5% ±1digit | |
| Standard solutions automatically detected (@25°C) | 1.679pH - 2.000pH - 4.000pH - 4.008pH 4.010pH - 6.860pH - 6.865pH - 7.000pH 7.413pH - 7.648pH - 9.180pH - 9.210pH 10.010pH | | |
| <i>mV measurement by instrument</i> | | <i>Automatic/manual temperature compensation</i> | |
| Measuring range | -1999.9...+1999.9mV | 0...100°C with α _T = 0.00...4.00%/°C | |
| Resolution | 0.1mV | Reference temperature 0...50°C | |
| Accuracy | ±0.1mV ±1digit | Conversion factor χ/TDS 0.4...0.8 | |
| Drift after 1 year | 0.5mV/year | Cell constant K (cm ⁻¹) already set on instrument 0.01 - 0.1 - 0.5 - 0.7 - 1.0 - 10.0 | |
| | | Cell constants K(cm ⁻¹) that can be set by user 0.01...20.00 | |
| <i>Conductivity measurement by instrument</i> | | <i>Standard solutions automatically detected (@25°C)</i> | |
| Measuring range (Kcell=0.01) / Res. | 0.000...1.999μS/cm | 147μS/cm 1413μS/cm 12880μS/cm 111800μS/cm | |
| Measuring range (Kcell=0.1) / Res. | 0.00...19.99μS/cm | | |
| Measuring range (K cell=1) / Res. | 0.0...199.9μS/cm 200...1999μS/cm 2.00...19.99mS/cm 20.0...199.9mS/cm | | |
| Measuring range (Kcell=10) / Res. | 200...1999mS/cm | <i>Measurement of temperature by instrument</i> | |
| Accuracy (conductivity) | ±0.5% ±1digit | Pt100 measuring range -50...+150°C Pt1000 measuring range -50...+150°C Resolution 0.1°C Accuracy ±0.1°C ±1digit Drift after 1 year 0.1°C/year | |

(*) The resistivity measurement is obtained from the reciprocal of conductivity measurement. Close to the bottom of the scale, the indication of resistivity appears like reported in the table below:

| K cell = 0.01 cm⁻¹ | | K cell = 0.1 cm⁻¹ | |
|--------------------------------------|---------------------|-------------------------------------|--------------------|
| Conductivity (μS/cm) | Resistivity (MΩ·cm) | Conductivity (μS/cm) | Resistivity(MΩ·cm) |
| 0.001 μS/cm | 1000 MΩ·cm | 0.01 μS/cm | 100 MΩ·cm |
| 0.002 μS/cm | 500 MΩ·cm | 0.02 μS/cm | 50 MΩ·cm |
| 0.003 μS/cm | 333 MΩ·cm | 0.03 μS/cm | 33 MΩ·cm |
| 0.004 μS/cm | 250 MΩ·cm | 0.04 μS/cm | 25 MΩ·cm |
| ... | ... | ... | ... |

ORDERING CODES

HD2256.2: The kit is composed of: instrument HD2256.2 for the measurement of pH - redox - conductivity - resistivity - TDS - salinity - temperature, **datalogger**, stabilized power supply at mains voltage 100-240Vac/12Vdc-1A., instructions manual and software DeltaLog11.

pH/mV electrodes, conductivity probes, dissolved oxygen probes, temperature probes, standard reference solutions for different measurement types, connection cables for pH electrodes with S7 connector, cables for data download to PC or printer have to be ordered separately.

ACCESSORIES**9CPRS232:** Connection cable SubD female 9- pole for serial output RS232C.**CP22:** USB 2.0 connection cable - connector type A - connector type B.**DeltaLog11:** Software for download and management of the data on PC using Windows 98 to Vista operating systems.**SWD10:** Stabilized power supply at 230Vac/9Vdc-300mA mains voltage.**HD40.1:** Portable, serial input, 24 column thermal printer, 57mm paper width.**HD40.2:** 24-column portable thermal printer, **Bluetooth and serial interface**, 57mm paper width, four NiMH 1.2V rechargeable batteries, SWD10 power supply, instruction manual, 5 thermal paper rolls. Requires the module **HD22BT (optional)** or the cable **HD 2110 CSNM (optional)**.**HD22.2:** Laboratory electrode holder composed of basis plate with incorporated magnetic stirrer, staff and replaceable electrode holder. Height max. 380mm. Powered by bench-top meters of the series HD22... with cable **HD22.2.1 (optional)** or supplier **SWD10 (optional)**.**HD22.3:** Laboratory electrode holder with metal basis plate. Flexible electrode holder for free positioning. For Ø 12mm probes.**HD22BT:** Bluetooth module for wireless data transmission from instrument to PC. **The fitting of the module into the instrument is made exclusively by Delta Ohm, at the time of placing the order.****TP47:** Module for the connection of Pt100 4-wire and Pt1000 2-wire probes.**pH electrodes without SICRAM module (Inputs ① and ②)****KP20:** Combined pH electrode for general use, gel filled with screw connector S7 body in Epoxy.**KP30:** Combined pH electrode for general use, cable 1 m, gel filled, body in Epoxy.**KP50:** Combined pH electrode with Teflon collar diaphragm, for emulsions, deionised water, S7 screw connector, gel filled, body in glass.**KP 61:** Combined pH electrode, 3 diaphragms for milk, cream, etc. Liquid reference filling, with screw connector S7, body in glass.**KP 62:** Combined pH electrode, 1 diaphragm for pure water, paints, etc. gel-filled, with screw connector S7, body in glass.**KP 63:** Combined pH electrode for general use, varnish, cable 1 m, electrolyte KCl 3M body in glass.**KP 64:** Combined pH electrode for water, varnish, emulsions, etc., electrolyte KCl 3M with screw connector S7, body in glass.**KP 70:** Combined pH micro electrode diam. 4.5 x L=25 mm. Gel filled, with screw connector, body in glass.**KP 80:** Combined pointed pH electrode, gel filled, with screw connector S7, body in glass.**KP100:** Flat membrane gel combined pH electrode with S7 screw connector, glass body, for skin, leather, paper.**CP:** Extension cable 1.5m with BNC connectors on one side and S7 on the other side for electrode with S7 connector.**CP5:** Extension cable 5m with BNC connectors on one side and S7 on the other side for electrode with S7 connector.**CE:** S7 screw connector for pH electrode.**BNC:** Female BNC for electrode extension.**pH electrodes with SICRAM module (Input ③)****KP63TS:** Combined pH/temperature electrode with SICRAM module, body in Epoxy, Ag/AgCl sat KCl.**SICRAM Module with BNC input for pH electrodes (Input ③)****KP47:** SICRAM module for pH electrode with BNC standard connector.**Electrode characteristics at page 401****ORP Electrodes (Inputs ① and ②)****KP90:** Redox Platinum electrode, with screw connector S7, electrolyte KCl 3M, body in glass.**KP91:** Redox Platinum electrode with 1m cable, GEL filled, body in glass.

X



mV

pH buffer solutions**HD8642:** Buffer solution 4.01pH - 200cc.**HD8672:** Buffer solution 6.86pH - 200cc.**HD8692:** Buffer solution 9.18pH - 200cc.**Redox buffer solutions****HDR220:** Redox buffer solution 220mV 0,5 l.**HDR468:** Redox buffer solution 468mV 0,5 l.**Electrolyte solutions****KCL 3M:** 50cc ready for use solution for electrode refilling.**Cleaning and maintenance****HD62PT:** Diaphragm cleaning (tiourea in HCl) - 500ml.**HD62PP:** Protein cleaning (pepsin in HCl) - 500ml.**HD62RF:** Regeneration (fluorhydric acid) - 100ml.**HD62SC:** Solution for electrode preservation - 500ml.**Conductivity probes and combined conductivity and temperature probes without SICRAM module (Input ②)****SP06T:** Combined conductivity and temperature 4-electrode cell in Platinum, body in Pocan. Cell constant K = 0.7. Measurement range 5µS/cm ...200mS/cm, 0...90°C.**SPT401.001:** Combined conductivity and temperature 2-electrode cell in stainless steel AISI 316. Cell constant K = 0.01. Measurement range 0.04µS/cm ...20µS/cm, 0...120°C. Measurement in closed-cell.**SPT01G:** Combined conductivity and temperature 2-electrode Platinum-wire cell, body in glass. Cell constant K = 0.1. Measurement range 0.1µS/cm ...500µS/cm, 0...80°C.**SPT1G:** Combined conductivity and temperature 2-electrode Platinum-wire cell, body in glass. Cell constant K = 1. Measurement range 10µS/cm ...10mS/cm, 0...80°C.**SPT10G:** Combined conductivity and temperature 2-electrode Platinum-wire cell, body in glass. Cell constant K = 10. Measurement range 500µS/cm ...200mS/cm, 0...80°C.**Combined conductivity / temperature probes with SICRAM module (Input ③)****SPT1GS:** Combined conductivity /temperature 2-electrode Platinum- wire cell, body in glass with SICRAM module. Cell constant K = 1. Measuring range 10µS/cm ...10mS/cm, 0...80°C.**Electrode characteristics at page 402****Standard conductivity calibration solutions****HD8747:** Standard calibration solution 0.001mol/l equal to 147µS/cm @25°C - 200cc.**HD8714:** Standard calibration solution 0.01mol/l equal to 1413µS/cm @25°C - 200cc.**HD8712:** Standard calibration solution 0.1mol/l equal to 12880µS/cm @25°C - 200cc.**HD87111:** Standard calibration solution 1mol/l equal to 111800µS/cm @25°C - 200cc.**Temperature probes complete with SICRAM module (Input ③)****TP87:** PT100 sensor immersion probe. Stem Ø 3 mm, length 70 mm. Cable length 1 m.**TP4721.0:** Pt100 sensor immersion probe. Stem Ø 3 mm, length 230 mm. Cable length 2 m.**TP473P.0:** Pt100 sensor penetration probe. Stem Ø 4mm, length 150 mm. Cable length 2 m.**TP474C.0:** Pt100 sensor contact probe. Stem Ø 4mm, length 230mm, contact surface Ø 5mm. Cable length 2 m.**TP475A.0:** Air probe, sensor Pt100. Stem Ø 4mm, length 230mm. Cable length 2 m.**TP4721.5:** Immersion probe, sensor Pt100. Stem Ø 6mm, length 500 mm. Cable length 2 m.**TP4721.10:** Immersion probe, sensor Pt100. Stem Ø 6mm, length 1,000mm. Cable length 2 m.**Temperature probes complete with TP47 module (input ③)****TP47.100:** Direct 4 wires Pt100 sensor immersion probe. Probe's stem Ø 3mm, length 230mm. Connection cable 4 wires with connector, length 2 m.**TP47.1000:** Pt1000 sensor immersion probe. Probe's stem Ø 3mm, length 230mm. Connection cable 2 wires with connector, length 2 m.**TP87.100:** Pt100 sensor immersion probe. Probe's stem Ø 3mm, length 70mm. 4 wire connection cable with connector, length 1 m.**TP87.1000:** Pt1000 sensor immersion probe. Probe's stem Ø 3mm, length 70mm. 2-wire connection cable with connector, length 1 m.**Accessories****TP47:** Module for the connection of Pt100 4-wire and Pt1000 2-wire probes.