



## HD 25.2 BENCH-TOP TURBIDITY METER

The **HD25.2** is a digital turbidity meter for laboratory and mobile use, suitable for measurements in drinking water, waste water and process liquids. The working principle is based on the nephelometric (90° scattered light sensor) method.

It is equipped with three light detectors and two LED light sources (white and infrared) which are permanently kept under control in order to guarantee long-term stability. The instrument performs measurements according to the standards **EPA 180.1**, **ISO-NEPH (ISO 7027)**, **EBC** and **ASBC**. It is also able to carry out measures of transmission factor percentage of white and infrared light.

The initial factory calibration is based on Forazin primary standard. For routine calibration a set of stabilized secondary standard solutions is available: STCAL (Turbidity standards for calibration):

- **STCAL 1** less than 0,05 NTU
- **STCAL 2** equal to 8 NTU
- **STCAL 3** equal to 80 NTU
- **STCAL 4** equal to 800 NTU



User Calibration is automatic on one, three or four points, depending on the measuring variable.

Stabilized power supply and advanced electronics guarantee optimal performances over time. The HD25.2 is a **datalogger** that stores up to 999 samples.

The data can be transferred from the instrument connected to a PC via the multi-standard RS232C serial port and USB 2.0.

The RS232C serial port can be used to transfer the acquired measurements to a 24 column printer.

The Print function allows to print labels with progressive numeration and automatic incrementation, with all data related to the sample being examined.

The dedicated software **DeltaLog11** allows instrument management and data processing on PC.

The use of the HD25.2 by more customers is facilitated by the "User Management" function, which allows, according to the case, to enable or disable some advanced functions of the instrument through password.

**The protection degree is IP66.**

### Technical characteristics

#### Instrument

Dimensions (Length x Width x Height)	220x120x55mm
Weight	400g (batteries included)
Materials	ABS
Display LCD	4½ characters plus symbols Visible area: 52x42mm

#### Operating conditions

Instrument working temperature	0 ... 50°C
Storage temperature instrument	-25 ... 65°C
Working relative humidity	0 ... 90% R.H. without condensation
Storing of Calibration standards	5...25°C (temperature should not exceed, protect from light)

#### Protection degree

IP66
------

#### Power supply

Batteries	3 1,5 V AA type batteries
Autonomy	100 hours with 1800mAh alkaline
Rete (cod. <b>SWD10</b> )	Mains adapter 100-240Vac/12Vdc-1A

#### Measuring methods

Standard	EPA180.1, ISO-NEPH (ISO 7027), EBC, ASBC, WHITE %T e IR %T
Light source	LED IR (850nm) and white LED (470nm)
Receiver	Silicium photodiode
Sample cell	Ø24mm - height 68mm, 20cc



**Measurement of turbidity**

Method / Measuring range

EPA180.1	(0...1000 NTU)
ISO-NEPH	(0...1000 FNU)
EBC	(0...250 EBC)
ASBC	(0...9999 ASBC)
WHITE %T	(0...100 %T)
IR %T	(0...100 %T)
Resolution	0.01 NTU (0...9.99 NTU)
	0.1 NTU (10.0...99.9 NTU)
	1 NTU (100...1000 NTU)
Accuracy	±2% reading + 0.01 NTU (0...500 NTU)
	±3% reading (500...1000 NTU)
Repeatability	±2% reading or 0.01 NTU (the major one)

**Security of memorized data**

Unlimited

**Time**

Date and hour

real time schedule

Accuracy

1min/month max error

**Measured values storing**

Quantity

999 samples

**Serial interface RS232C**

Type

RS232C electrically isolated

Baud rate

Can be set from 1200 to 38400 baud

Data bit

8

Parity

None

Stop bit

1

Flow Control

Xon/Xoff

Serial cable length

Max 15m

**USB interface**

Type

1.1 - 2.0 electrically isolated

**Connections**

Serial interface

DB9 connector (9- pole male)

USB interface

USB connector type B

Mains adapter

2- pole connector (Ø5.5mm-2.1mm). Positive at centre.

**Ordering codes**

**HD25.2K:** The kit is composed of: instrument HD25.2, 4 empty cells, 4 calibration standards STCAL, 3 1.5Vdc alkaline batteries, lubricant rag, 25cc Silicon oil, instructions manual, carrying case and software DeltaLog11 for PCs running Windows 98 to Vista.

**Accessories****9CPRS232:** Connection cable SubD female 9- pole for serial output RS232C**CP22:** Connection cable USB 2.0 connector type A - type B**SWD10:** Stabilized power supply at 230Vac/9Vdc-300mA mains voltage.**HD40.1:** Portable, serial input, 24 column thermal printer, 57mm paper width.**PL:** Lubricant rag**OS1:** Silicon oil - 25cc.**KCV:** 4 empty sample cells Ø24x68mm**Turbidity calibration standards****STCAL 1:** Calibration standard with low turbidity formazin reference less than 0,05 NTU.**STCAL 2:** Calibration standard with reference formazin 8 NTU - 20cc.**STCAL 3:** Calibration standard with reference formazin 80 NTU - 20cc.**STCAL 4:** Calibration standard with reference formazin 800 NTU - 20cc.**KS:** Kit 4 calibration standard with reference formazin STCAL 1, STCAL 2, STCAL 3, STCAL 4.

HD40.1



ASBC



FNU



EBC



NTU